



By Appointment to Her Majesty Queen Elizabeth II
Manufacturers of French Polishes, Stains and Wax Polishes
since Mylands Limited, London

MYLANDS

OF LONDON

Bespoke Paint & Wood Finishes

PRODUCT DATA SHEET

Quick Drying Interior & Exterior Varnish

General:	Quick Drying Interior & Exterior Varnish is a premium quality clear water based alkyd varnish for interior and exterior use on wood and wood based substrates. Formulated to resist moisture, staining and general wear & tear.	
Product Codes:	Product:	Product code
	QD Interior & Exterior Varnish Matt	12 600 3010
	QD Interior & Exterior Varnish Satin	12 600 3030
	QD Interior & Exterior Varnish Gloss	12 600 3090
Technical Data:	Quick Dry Interior & Exterior Varnish is a water based alkyd varnish for use on timber and wood based substrates. QD Varnish is available in three sheen levels, Matt, Satin and Gloss. The Matt finish, in common with other matt finishes, has a lower durability than the Satin & the Gloss. The product's speed of dry allows for two coats to be applied in one day. QD Varnish is low odour and environmentally friendly. It also has good yellowing resistant properties. QD Varnish is completely washable and offers excellent resistance to mechanical damage when fully cured.	
Application:	Quick Dry Interior & Exterior Varnish may be brush or roller applied. Stir well before use. Do not use in extremes of temperature or humidity. Do not use below 10c or above 30c. Do not use above 75% humidity. Do not apply if rain or poor weather is imminent. Ensure surfaces are sound, clean and dry before sanding. If applying over bare wood, apply a thin even coat as a primer sealer. (Thin with up to 10% water if required.) Apply at least another two or more coats depending on desired finish. If applying over a good condition varnished surface (lightly denib first), apply a minimum of two coats over hard wood and three over soft wood.	
Drying Time:	The drying times quoted are at 20c & will vary with temperature. Touch Dry: 2-3 hrs Recoat time: 3-4hrs	
Coverage:	The coverage will vary depending on absorbency of the substrate, but should be an average of 8-10 square metres per litre.	
Thinners:	QD Interior and Exterior Varnish is supplied ready for use, If thinning is required, thin with up to 10% water.	
Equipment	Wash brushers/rollers in warm water containing a little detergent immediately after use.	

cleaning	
Packaging:	QD Interior and Exterior Varnish is available in 1 and 2.5 litre containers.
Physical Constants:	VOC level: 30g/l
Storage:	Store above 10°C & below 30°C. Protect from frost.
Shelf life:	Up to 18 months.
Health and Safety:	Refer to Mylands MSDS before use.

Last Updated December 2014

For further information contact Mylands Head Office on 0208 670 9161 or look on the website – www.mylands.co.uk