



By Appointment to Her Majesty Queen Elizabeth II  
Manufacturers of French Polishes, Stains and Wax Polishes  
John Mylands Limited, London

# MYLANDS

ESTABLISHED LONDON 1884

## PRODUCT DATA SHEETS MARBLE MATT EMULSION PAINT

|                           |  |                                    |                    |
|---------------------------|--|------------------------------------|--------------------|
| <b>General</b>            | A white acrylic matt emulsion for interior use.  |                                    |                    |
| <b>Product Codes</b>      | <b>Product</b><br>Marble Matt Emulsion   | <b>Product code</b><br>50 600 0001 | <b>Sheen</b><br>3% |
| <b>Technical Data</b>     | <p>This is a waterbased acrylic emulsion paint for interior use.<br/>This product is not suitable for woodwork.<br/>(Except painted decorative furniture, apply wax on top of emulsion).<br/>The product's speed of dry allows for two coats to be applied in one day.<br/>The product is low odour and environmentally friendly.<br/>It has excellent coverage properties.<br/>It is washable.<br/>This emulsion is available in white only from stock, but may be tinted to a colour on request.</p> |                                    |                    |
| <b>Application</b>        | <p>Stir well before use.<br/>Do not use in extremes of temperature. Use between 8°C and 30°C.<br/>Before use clean surfaces to be painted ensuring any grease, dirt or flakes are removed.<br/>This product is formulated for brush or roller application.</p>   |                                    |                    |
| <b>Drying Time</b>        | <p>Touch dry: 1 – 2 hours.<br/>Recoat time: 3 – 4 hours.</p>   |                                    |                    |
| <b>Coverage</b>           | The coverage should be an average of 15m <sup>2</sup> per litre on an already sealed surface.  |                                    |                    |
| <b>Thinners</b>           | <p>On porous surfaces (e.g. bare plaster) thin the first coat with up to 30% water.<br/>On slightly porous surfaces thin the first coat with up to 15% water.<br/>This paint has a high pigmentation. It can be thinned up to 45% and still be used as a second or third coat for a fine finish.</p>   |                                    |                    |
| <b>Equipment Cleaning</b> | Wash brushes/rollers immediately after use, in warm water containing a little detergent.   |                                    |                    |
| <b>Packaging</b>          | This product is available in 1 litre, 2.5 litre and 5 litre containers.  |                                    |                    |
| <b>Storage</b>            | <p>This product must be protected from frost.<br/>Store at temperature above 5°C.<br/>Use within 12 months.</p>  |                                    |                    |
| <b>Health and Safety</b>  | Refer to Mylands MSDS before use.  |                                    |                    |

Updated 20.06.2014

For further information visit our website [www.mylands.co.uk](http://www.mylands.co.uk) or contact us: +44 (0)208 670 9161 [sales@mylands.co.uk](mailto:sales@mylands.co.uk)