

# MYLANDS

ESTABLISHED LONDON 1884

## PRODUCT DATA SHEETS METAL PRIMER AND UNDERCOAT (ANTI CORROSIVE)

<b>General</b>	A good quality white water based primer/undercoat for metal which is suitable for interior and exterior use.		
<b>Product Codes</b>	<b>Product</b> Metal Primer and Undercoat White	<b>Product code</b> 50 200 0005	<b>Sheen</b> n/a
<b>Technical Data</b>	<p>This is a water based alykd primer/undercoat for use on metal substrates. It replaces oil based primers.</p> <p>The primer has anti-corrosive properties. It is suitable for interior and exterior use.</p> <p>The product's speed of dry allows for two coats to be applied in one day. The primer is low odour.</p> <p>The primer is available in white only from stock but light and dark grey available on request.</p>		
<b>Application</b>	<p>Stir well before use.</p> <p>Do not use in extremes of temperature. Use between 8°C to 30°C. Do not apply when rain or dew is imminent.</p> <p>This product is formulated for brush or roller application.</p>		
<b>Drying Time</b>	<p>Touch dry: 1 – 2 hours.</p> <p>Recoat time: 3 – 4 hours.</p>		
<b>Coverage</b>	The coverage should be an average of 10 – 12m <sup>2</sup> per litre.		
<b>Thinners</b>	Should it be deemed necessary to thin, water should be used up to a level of 10%.		
<b>Equipment Cleaning</b>	Wash brushes/rollers immediately after use, in warm water containing a little detergent.		
<b>Packaging</b>	These products are available in 1 litre, 2.5 litre and 5 litre containers.		
<b>Storage</b>	<p>This product must be protected from frost.</p> <p>Store at temperature above 5°C.</p> <p>Use within 12 months.</p>		
<b>Health and Safety</b>	Refer to Mylands MSDS before use.		