



By Appointment to Her Majesty Queen Elizabeth II
Manufacturers of French Polishes, Stains and Wax Polishes
John Mylands Limited, London

MYLANDS

ESTABLISHED LONDON 1884

PRODUCT DATA SHEETS WAX TOLUENE FREE

General	These waxes have superseded the Toluene Based waxes as the most popular wax for the pine trade.	
Product Codes	Product Colour	Product Code
	Clear (T.F.)	16 786 8200
	Antique Brown (T.F.)	16 786 8473
	Rustic Brown (T.F.)	16 786 8210
	K Brown (T.F.)	16 786 8205
	Old Pine (T.F.)	16 786 8490
	Stripped Pine M7 (T.F.)	16 786 8479
	Quick Dry Dark Pine (T.F.)	16 786 8805
Technical Data	<p>These waxes are formulated on slower solvents than the toluene based waxes which they will eventually replace and give excellent build and shine on pine furniture.</p> <p>They are formulated away from toluene solvent, which has received adverse publicity in recent years.</p> <p>Similar colours are also available in the toluene based formulation see separate Data Sheet – ‘Toluene Based Waxes’.</p> <p>Clear Wax is now available toluene-free.</p> <p>Stripped Pine M7 – original colour and the Industry standard on pine.</p> <p>Antique Brown – second most popular pine colour, being slightly warmer than M7 a golden orange-brown tone.</p> <p>Rustic Brown – a darker version of Stripped Pine M7.</p>	
Application	<p>These waxes may be applied to bare timber or used over a base stain.</p> <p>The following are suitable for use under this range of waxes: Light Fast Stains, Rich Stains, Non Fade Ground Stains, Waterbased Stains.</p> <p>The stain must be dry before application of the wax. See individual stain Data Sheets for drying time.</p> <p>Apply wax using a brush or a clean white lint-free cloth and buff off with another clean cloth.</p> <p>These waxes may also be sprayed by an experience wax sprayer using a high power airless (wax) spray pump. Please consult Mylands Technical Department before spraying for the first time.</p>	
Drying Time	Drying time will be dependant on coating thickness applied and ambient temperature but should be no more than 30 minutes at 20°C.	
Coverage	Coverage will depend on porosity of timber used and coating thickness applied.	
Packaging	These waxes are normally available in 400 gram 5 litre and 20 litre containers.	
Physical Constants	VOC Level:	
Storage	Replace container lid after use and store in a cool place.	
Health and Safety	Refer to Mylands Toluene-free Wax MSDS before use.	

Updated 17.03.2015

For further information visit our website www.mylands.co.uk or contact us: +44 (0)208 670 9161 sales@mylands.co.uk